
Ŧ	L D	н <b>т</b>	m	0







LAYOUT SHOWN AS

Keying Shown as example

F

## CHARACTERISTICS

Н

ω


 $\sim$ 

-Standard : Based on MIL-DTL-38999 Series III

-Shell Material	: Aluminium						
-Shell Plating	: Black Zinc Nickel						
-Insulator	: Thermoplastic						
-Contacts	: Copper Alloy						
-Seals & Grommet	: Silicon Elastomer						
-Contact Plating	: Gold over copper Alloy 0.8µm minimum						
-Durability	: 500 Mating cycles						
-Delivered with Souriau contacts and Accessories							
-Temperature Range	: -65℃ to +175℃						
Calt Corror	. FOO hours						

Connector dimension					
Dim	Nominal				
Р	3.25±0.2				
РР	4.93±0.2				
R1	23.01				
R2	20.62				
S	28.6±0.3				
V	20.83+0/-1.25				
W	2.1/2.5				
Z	31.5 Max				
VV THREAD	M18x1-6g				

Е





-Temperature Range	: -65°C to +175°C									
-Salt Spray	: 500 hours									
-Mass	: 19.49 g ± 10%									
BASIC SERIES:	8D 0	- 13	z	04	В	D				
SHELL TYPE : Square Flange Receptacle										
CONTACT TYPE : Sta	ndard Crimp Contact							OR	IENTATION	: D
SHELL SIZE : 13							CONTACT TY	PE : SOCKET	(500 Matin	igs)
PLATING : Z =	Black Zinc Nickel							CONTACT L	AYOUT : 13	-04

G

	Ξ		А					
					4			
	1							
	10/ 1							
	0							
		1						
S EXA	AMPLE				3			
	non-conformit							
	ch does not co							
	of the Parties or by a third party							
	,							
untry FR	Jurisd	liction & Cont Not Listed	rol List	]	2			
371	204BD							
					-			
		CUSTOMER	RDRAWING	MOD N°	<u> </u>			
um	Receptacl	ie od serie	es					
ar :			PROJECT					
			59	oottu of	1			
	This document is the property of SOURIAU							
J.U.	LOIN it must not be reproduced or							
	communicated without permission							
	DRG N°			SHEET				
Z04	4BD-C			1/2	J			
	В		А					

ſ	т	۵	н <b>т</b>	m		0	
		Contact Layout					Panel Cutout
4		$X \begin{pmatrix} D \\ D \\ D \\ D \\ D \\ D \\ T \\ T \\ T \\ T \\$			1	SQUARE FLANGE RECEPTACLE (TYPI REAR MOUNTING	E 0)
	Cont positio A B C C D Shell Arrangement N Size no. 13 -4	n ID  (mm)  (mm)    + .000 (0.00)  +.150 (3.81)    + .146 (3.71)  +.035 (0.89)    + .000 (0.00)  -083 (2.11)   146 (3.71)  +.036 (0.89)			¥ ~		
ω							Dim ØA ØAA R1 ØT
						SOURIAU shall not due to a use of t the Specifications iss (professiona	the Products whi
N						PN	Country FR
					A 16-10-20 ISS DATE Designed By:	16 First Release Latest modification - Date:	by
<u> </u>					TITLE SCALE NA		Aluminium General linear Tolerances: ±
					SOURIA		OURIAU.C
					FORMAT A3		SOURIAU 8D013Z0
L	Н	G	F	E	D	С	

