Ξ			0	ω]
	S The second sec					
			LAYOUT SHO	OWN AS EXAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension	7				
Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 25 Max]				
-Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	Z' 31.5 Max VV THREAD M15x1-6g	3	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer					& Control List	
-Contact Plating : Gold over copper Alloy 0.8µm minimum				FR Not	Listed	
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D511M04PCL			
-Temperature Range : -65°C to +200°C		Δ 16	10-2016 First Release			
-Salt Spray : 2000 hours						<u> </u>
Mass : 12 g ± 10%		ISS I Designed By:	DATE Latest modification - by Date:	CUS	TOMER DRAWING	<i>i</i> N
		тіті	Composite Plug 8D series			
BASIC SERIES: 8D 5 - 11 M	04 P C L	SCALE		ral linear N rances:	IPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding	Delivered V	V/O Contacts NA		±	859 This document is the property of	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORII CONTACT TYPE : PIN(ENTATION : C SOUR	RIAU WWW.SOUF		SOURIAU it must not be reproduced or	
					communicated without permission SHE	
PLATING : M = Nickel	CONTACT LA	YOUT: 11-04 A3		IRIAU DRG N° 11M04PCL-C	1/3	
			- OU3		±/.	

ſ		<mark>۵</mark>	г	m		0	
		Contact Layout					
4	×	$ \begin{array}{c} \bullet \\ \bullet \\$					
	Shell Arrangement Numb	X-axis Y-axis (mm) +065 (1.65) .065 (1.65) +065 (1.65) .065 (1.65) -065 (1.65) .065 (1.65) -065 (1.65) .065 (1.65) -065 (1.65) .065 (1.65) -065 (1.65) .065 (1.65) -065 (1.65) .065 (1.65) -065 (1.65) .065 (1.65) -065 (1.65) .065 (1.65)					
ω	11 -4 4	i 20 I All MS20050-4	J				
	+					SOURIAU shall not be liab due to a use of the Pro- the Specifications issued by (professional recon	ducts w either c
N						PN: 8D5	Count FR
					A 16-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:	
_					SCALE NA	Genera Tolera ±	ances:
					SOURIA		
					FORMAT A3	SOU 8D5:	RIAL 11M
	Н	G	F	E	D	C	

			4		
			3		
any non-conformi which does not co r of the Parties or dation, technical n ntry Juriso R MO4PCL	mply with by a third party		2		
	CUSTOMER DRAWING	MOD N°	·		
posite Plug 8D series					
r	NPRDS / PROJECT 859				
.COM	This document is the property of				
U DRG N° ⁄I04PCL-C		SHEET			
B	A]		

Þ

ω