<u>т</u>	۵	н т	m	C	-	0	Ξ		
	Z	ØS							
						LAYOUT SHO	WN AS EXAMPLE		
		Keying Show	n as example						
CHARACTERISTICS			Connector dimension	7					
Standard : Based on MIL-E			Dim Nominal ØS 25 Max	_					
-Shell Plating : C -Insulator : T	Aluminium Olive drab Cadmium Thermoplastic Copper Alloy		Z 31 Max VV THREAD M15x1-6g			the Specifications issued by	ducts which does not con	mply with y a third party	
-Seals & Grommet : S	Silicon Elastomer	imum			L		Country Jurisdi FR	iction & Control List	
	ability : 500 Mating cycles					Not Listed			
-Delivered with Souriau co	ntacts and Accessories					PN: 8D	511W22BD		
-	-65°C to +175°C			Γ	A 18-10-2016	5 First Release			
	500 hours			-	ISS DATE	Latest modification - by			MOD N°
Mass : 1	16.89 g ± 10%			_	Designed By:	Date:		CUSTOMER DRAWING	
					TITLE	F	Aluminium Plug 80	D series	
BASIC SERIES:	8D 5 - 11	1 W 22 B D	I	_	SCALE	Genera	al linear	D series	
BASIC SERIES: SHELL TYPE : Plug with RF		1 W 22 B D		_		Genera		NPRDS / PROJECT 859	
	FI Shielding	1 W 22 B D	ORIE	ENTATION : D	SCALE NA	Genera Toler	al linear ances: 	NPRDS / PROJECT 859 This document is the prop SOURIAU	
SHELL TYPE : Plug with RF	FI Shielding	1 W 22 B D	ORIE CONTACT TYPE : SOCKET(SCALE	Genera Toler	al linear ances: 	NPRDS / PROJECT 859 This document is the prop	ed or
SHELL TYPE : Plug with RF CONTACT TYPE : Standar	FI Shielding rd Crimp Contact	1 W 22 B D	CONTACT TYPE : SOCKET(SCALE NA	Genera Toler. ± WWW.SOUR	al linear ances: 	NPRDS / PROJECT 859 This document is the prop SOURIAU it must not be reproduce	ed or

		۵	н т	m		0	
4		Contact Layout 22*					
 دى	Ctc A B C D	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905					
						SOURIAU shall not be lia due to a use of the Pr the Specifications issued b (professional reco	oducts w
N						PN: 80	Coun FR 0511
_					A 18-10-2016 ISS DATE Designed By:	6 First Release Latest modification - by Date:	
-					SCALE NA SOURIAU	Gener Tole	Alumi ral linear erances: ±
					FORMAT		JRIAU

G

Н

F

Е

A3

D

С

