	G	т.	m	τ	-	0			
	MA Thread	S							
						LAYOUT SHO	OWN AS EXAMPLE		
		Keying Shown as	s example						
CHARACTERISTICS		Г	Connector dimension	7					
-Standard : Based on MIL-DTL-38		F	DimNominalØS25 Max						
-Shell Material : Alumin -Shell Plating : Olive d -Insulator : Thermo -Contacts : Copper	Irab Cadmium oplastic		Z 31 Max VV THREAD M15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet : Silicon	Elastomer						Country Jurisd	iction & Control List]
_	ver copper Alloy 0.8µm minimum ating cycles				FR Not Listed				
-Delivered with Souriau contacts						PN: 80	0511W22SD		
-Temperature Range : -65°C t	to +175°C			Γ	A 18-10-2016	6 First Release]
-Salt Spray : 500 ho									
-Mass : 16.89 g	;±10%			-	ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWING	MOD N°
					TITLE Aluminium Plug 8D series				
BASIC SERIES:	8D 5 - 11 W	22 S D		-	SCALE		ral linear rances:	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shiel	ding				NA		±	859 This document is the prop	perty of
				SOURIAU WWW.SOURIAU.COM it must not be reproduced or communicated without permissi			ed or		
			CONTACT TYPE : SUCKET(5	ou watings)				communicated without pe	rmission
SHELL SIZE : 11				(0) T (1) (0)	FORMAT				CULCET
	Cadmium		CONTACT LAY	/OUT : 11-22	FORMAT A3		IRIAU DRG N° 511W22SD-C		SHEET 1/2

	T	<u>م</u>	п П	m	D	0
4		Contact Layout 22*				
 ت	Ctc A B C D	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905				
						SOURIAU shall not be liable for a due to a use of the Products v the Specifications issued by either (professional recommend
N						Coun FR PN: 8D511
					A 18-10-201 ISS DATE Designed By:	.6 First Release Latest modification - by Date:
_ _					TITLE SCALE NA	Alumi
					FORMAT	J WWW.SOURIAU.

G

Н

F

Е

A3

D

С

