١	ם ד	г	m		0	Β	A		
4		Dearth Thread						4	
ω			1		LAYOUT SI	HOWN AS EXAMPLE		3	
	CHARACTERISTICS	Keyin	g Shown as example						
	-Standard : Based on MIL-DTL-38999 Series III		Connector dimension Dim Nomin	al					
N	-Standard : Based on Mit-Dit-38999 Series III ØS 25 Max -Shell Material : Aluminium ØS 25 Max -Shell Plating : Black Zinc Nickel Z 31 Max -Insulator : Thermoplastic VV THREAD M15x1-6g -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Sum minimum				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed				
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessorie -Temperature Range <u>-65°C to +175°C</u>	25			PN: 8D511Z01AC				
	-Salt Spray : 500 hours			A 18	-10-2016 First Release				
_	-Mass : 14.98 g ± 10%			ISS Designed B	DATE Latest modification - by r: Date:	<u>с</u> і	MOD N	<u>۱°</u>	
					'LE	Aluminium Plug 8D series			
<u> </u>	BASIC SERIES:8D5SHELL TYPE: Plug with RFI Shielding	- 11 Z 01 A	C	SCALE NA		eral linear lerances: ±	NPRDS / PROJECT 859	1	
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 CONTACT TYPE : PIN(500 Mar)				SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission				
	PLATING : Z = Black Zinc Nickel		CONTAC	T LAYOUT : 11-01	SO	URIAU DRG N°	SHEET	г	
				A3	8	D511Z01AC-C	1/2		

r	I	G	н г	m	D	0
		Contact Layout				
4		01				
	(1#12 11-01	1			
ω	Ctc A	X Y 0 0				
	-					SOURIAU shall not be liable for any due to a use of the Products wh
N						the Specifications issued by either of (professional recommendat Countr FR
					A 18-10-20 ISS DATE Designed By:	PN: 8D5112 16 First Release Latest modification - by Date:
_					TITLE SCALE NA	Alumin General linear Tolerances: ±
					FORMAT A3	J WWW.SOURIAU.C SOURIAU 8D511Z0
Ĺ	Н	G	F	E	D	C C

