ی ت ب	т <u>п</u>		0	₩ >		
			LAYOUT SHOWN AS EX	CAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Without Plating -Insulator : Thermoplastic -Contacts : Copper Alloy	DimNominalØS29.4 MaxZ31 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer Contact Plating : Gold over copper Alloy 0.8μm minimum			CountryJurisdiction & Control ListFRNot Listed			
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D513X03BC			
-Temperature Range -65°C to +175°C		A 19-10-2016	First Release			
-Salt Spray : 2000 hours		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE	Composite Plug 8D series			
BASIC SERIES: 8D 5 - 13 X 0. SHELL TYPE : Plug with RFI Shielding	3 B C	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIENT/ CONTACT TYPE : SOCKET(500		SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			
PLATING : X = Without Plating	CONTACT LAYOU		FORMAT SOURIAU DRG N°			
			8D513X0		1/2	

r	Ŧ	D D		П	т	D		C	
		Contact Layout							
		03							
4									
	[3#16							
	Ctc A B	13-03 X 2.39 0	Y 1.47 -2.79						
ى	С	-2.39	1.47						
	L								
								due to a use the Specifications	not be liable for a of the Products v s issued by either onal recommend
N						L			Coun
								F	PN: 8D513
						A	10 10 2016	First Release	
						ISS	DATE	Latest modification	on - by
						Desig	ned By:	Date:	
							TITLE		Comp
<u> </u>							VA	\bigcirc	General linear Tolerances: ±
						sc	DURIAU	www	.SOURIAU.
						FO	RMAT		SOURIA

G

Н

F

Е

A3

D

С

