т   G			0	₿   >	•	]
A Linead						4
ω			LAYOUT SHOWN AS EXAMP	LE		3
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Keying Shown as example Connector dimension Dim Nominal	]				
-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	Shell Plating       : Black Zinc Nickel       Z       31 Max       UV THREAD       M18x1-6g         Insulator       : Thermoplastic             Contacts       : Copper Alloy             Seals & Grommet       : Silicon Elastomer					
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C			PN: 8D513Z26BD			
-Salt Spray : 500 hours 		A 19-10-2016 ISS DATE Designed By:	First Release Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		SCALE				-
BASIC SERIES: 8D 5 - 13 Z SHELL TYPE : Plug with RFI Shielding	26 B D	NA	General linear Tolerances: ±	NPRDS / PROJECT 859	roperty of	1
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIE CONTACT TYPE : SOCKET(5	NTATION : D SOURIAU	J WWW.SOURIAU.COM it must not be reproduced or communicated without permission			
PLATING : Z = Black Zinc Nickel	CONTACT LAY	YOUT : 13-26	SOURIAU DR 8D513Z26B		SHEET 1/2	
H G	FE	D	C	B A	<u> </u>	ł

-	<b></b>	G	н <b>г</b>	m	D	0
		Contact Layout				
4						
_		2#12 6#22D				
ω	Ctc A B C D E F 1 2	13-26         X       Y         0       3.47         2.47       4.34         2.47       -4.34         0       -3.47         -2.47       -4.34         -2.47       -4.34         3.25       0         -3.25       0				
	_					SOURIAU shall not be liable for an
22						due to a use of the Products wh the Specifications issued by either of (professional recommendat
						PN: 8D5132
_					A 19-10-202 ISS DATE Designed By:	16 First Release Latest modification - by Date:
					TITLE	Alumin
_					SCALE NA	General linear Tolerances:
					SOURIAU	J WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D513Z2
L	Н	G	F	E	D	С

