Ξ <u>Ω</u>	П	m	, t		0		Φ					
A	ØS									-		
	Keying Shown a				LAY	DUT SHOWN AS EXAMP	LE					
CHARACTERISTICS	F	Connector dimension										
-Standard : Based on MIL-DTL-38999 Series III Dim Nominal   -Shell Material : Composite ØS 35.7 Max   -Shell Plating : Nickel Z' 31.5 Max   -Insulator : Thermoplastic VV THREAD M25x1-6g   -Contacts : Copper Alloy . .   -Seals & Grommet : Silicon Elastomer . .   -Contact Plating : Gold over copper Alloy 0.8µm minimum . .					SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed							
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D517M22AA								
-Temperature Range <u>-</u> -65°C to +200°C			[	A 17-10-	2016 First Release					_		
-Salt Spray : 2000 hours				ISS DA	TE Latest modification	n - by			MOD N°	<u>,</u>		
				Designed By:	Date:		CUSTOMER DRAWING					
				TITLE		Composite	Plug 8D ser	ies				
→ BASIC SERIES: 8D 5 - 17 M SHELL TYPE : Plug with RFI Shielding	22 A A			SCALE NA		General linear Tolerances: ±	N	PRDS / PROJECT <b>859</b>				
CONTACT TYPE : Standard Crimp Contact		OR CONTACT TYPE : PIN	IENTATION : A	SOURI	AU WWW.	SOURIAU.COM	I	This document is the pro SOURIAU it must not be reprodu ommunicated without p	iced or			
SHELL SIZE : 17			,									
SHELL SIZE : 17 PLATING : M = Nickel		CONTACT L	AYOUT : 17-22	FORMAT		SOURIAU DR	G N°		SHEET			

	Ŧ	۵	н п	m		0	
4		Contact Layout 22					
<u>ل</u>	Ctc A B C D	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57 -6.32 0					
						SOURIAU shall not be liable due to a use of the Produ the Specifications issued by ei (professional recomm	ucts w ither c
м							Count FR
_					A 17-10-20 ISS DATE Designed By: TITLE	Date:	omp
_ <b>_</b>					SCALE NA SOURIA	General li Tolerand ±	linear ces:
	Н	G	F	E	FORMAT A3 D	SOUR 8D51	IAU

