| ; | ھ ہ | · | n | m | | 0 | Ξ | | | 7 |
|---|---|-----------------|-------------------------|----------------------------------|--------------|------------------------------|---|---|---------|---|
| 4 | | ØS- | | | | | | | | 4 |
| | | | | | | LAYOUT SHOW | WN AS EXAMPLE | | | 3 |
| | | | | | | | | | | |
| CUADACTE | | | Keying Shown as example | | | | | | | |
| CHARACTE | ased on MIL-DTL-38999 Series III | | Cor | nnector dimension Nominal | | | | | | |
| -Shell Mater -Shell Plating -Insulator -Contacts -Seals & Gro -Contact Pla | al : Aluminium : Olive drab Cadmium : Thermoplastic : Copper Alloy nmet : Silicon Elastomer | γ 0.8μm minimum | ØS Z VV THR | 35.7 Max 31 Max EAD M25x1-6g | | the Specifications issued by | ducts which does not com either of the Parties or by nmendation, technical no | nply with / a third party | | 2 |
| -Durability | -Durability : 500 Mating cycles | | | | | PN: 8D517W22BC | | | | |
| | -Delivered with Souriau contacts and Accessories | | | | | | | | | |
| -Temperatur -Salt Spray | e Range <u>-</u> -65°C to +175°C : 500 hours | | | | A 17-10-2016 | First Release | | | | |
| | . 500 110015 | | | | ISS DATE | Latest modification - by | | | MOD N° | |
| | | | | | Designed By: | Date: | | CUSTOMER DRAWING | | _ |
| TITLE Aluminium Plug | | | | luminium Plug 8D |) series | | | | | |
| BASIC SERIES | : 8D 5 : Plug with RFI Shielding | - 17 W 22 | ВС | | SCALE - | Genera Tolera ±- | inces: | NPRDS / PROJECT 859 | | - |
| | PE : Standard Crimp Contact | | | ORIENTATION : C | SOURIAU | WWW.SOUR | IAU.COM | This document is the pr SOURIAU it must not be reprod communicated without p | uced or | |
| | W = Olive drab Cadmium | | | CONTACT LAYOUT : 17-22 | FORMAT | SOUI | RIAU DRG N° | | SHEET | _ |
| | | I | | | A3 | | 17W22BC-C | | 1/2 | |
| | H G | | F | E | D | C | B | A | | |

| ſ | т | ۵ | н г | m | | 0 | |
|---|---------------|---|------------|------|-----------------------------------|---|--------------------------|
| 4 | | Contact Layout | | | | | |
| | Ctc A B | 2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 | | | | | |
| ى | C D | 0 -4.57 -6.32 0 | | | | | |
| | - | | | | | SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor | oducts w v either c |
| | | | | | A 17-10-20 | PN: 8D | |
| | | | | | ISS DATE Designed By: TITLE | Date: | Alumii |
| _ | | | | | SCALE NA SOURIA | | al linear ances: : |
| | | | | ,, , | FORMAT A3 | SOU 8D5 | RIAL |
| | Н | G | F | E | D | C | |

