Ŧ	۵	<del>ال</del> –		m			0				
4		ØS									2
							LAYOUT SH	OWN AS EXAMPLE			3
		Keying Sh	own as example								
CHARACTERISTICS			Connector								
	n MIL-DTL-38999 Series III		Dim	dimension Nominal							
-Shell Material	: Composite		ØS	35.7 Max		SOLIPIA	I I shall not he li	able for any non-conformi	ty or damage		
-Shell Plating	: Without Plating		Z VV THREAD	31 Max M25x1-6g				roducts which does not co			
-Insulator	: Thermoplastic							by either of the Parties or			
-Contacts	: Copper Alloy					(	professional rec	ommendation, technical n	otice.)		
-Seals & Grommet	: Silicon Elastomer										
► Contact Plating	: Gold over copper Alloy 0.8µm minim	um						Country Juriso	diction & Control List Not Listed		
		um									
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories					PN: 8D517X06SA					
-Temperature Range					A 18-1	10-2016 First Release	2				
-Salt Spray	: 2000 hours						1.6				_
	: 35.5 g ± 10%				ISS [ Designed By:		dification - by Date:		CUSTOMER DRAWING	MOD N°	<u> </u>
							Composite Plug 8				
					60115						
BASIC SERIES:	8D 5 - 17 vith RFI Shielding	X 06 S A	A		SCALE NA		<b>\</b>	eral linear erances: ±	NPRDS / PROJECT <b>859</b>		
				ORIENTATION : A					This document is the pr	roperty of	
SHELL SIZE : 17						SOURIAU WWW.SOURIAU.COM it must not be repro-					
PLATING : X =	Without Plating			CONTACT LAYOUT : 17-06	FORMAT			JRIAU DRG N°		SHEET	-
	without hatilig	I		CONTACT LATOUT . 17-00	A3					1/2	
		Γ		/				0517X06SA-C		1/2	
Н	G	F		E \T	D		С	B	A I		

	Т		D	г		т			0	
		Contac	ct Layout							
4		-x ( D + F	$ \begin{array}{c} \bullet \\ A \\ \oplus \\ \oplus \\ \end{array} \\ \end{array} \\ \begin{array}{c} \bullet \\ \bullet $							
		C	€Y ntacts gement 17-6) Location							
ယ	Shell Arr. size 17	A         +.121           B         +.241           C         +.000           D        241           E        121           F         +.000           no.         Number of contacts	m) (mm) 3.07) + 209 (5.31) (6.12) + 000 (0.00) (0.00) - 241 (6.12) (6.12) + 000 (0.00) (3.07) + 209 (5.31)							
									SOURIAU shall not b due to a use of th the Specifications issu	ne Products w ed by either c
2								[	(professional	recommenda Count FR
							A ISI Desi		First Release Latest modification - b Date:	: 8D517
							2			Compo General linear Tolerances:
4									WWW.SC	uriau.(
		T			1					OURIAU 8D517X
	Н		G	l F		E	D		С	

