

	BASIC SERIES: 8 SHELL TYPE : Plug with RFI Shielding	D 5	-	19	К	11	В	A				SCALE NA	-	$\exists \bigoplus$	
	CONTACT TYPE : Standard Crimp Con	tact									ORIENTATION	A SOUR	ΙΔΙΙ	WWW	
SHELL SIZE : 19										CONTACT TYPE : S	OCKET(500 Matin				
PLATING : K = Passivated						CONTACT LAYOUT : 19-11									
												A3			
	H	G					F			E		D		С	

	σ								
LAYOUT SHOWN AS EXA	MPLE				3				
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed									
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Plug 8D series General linear Tolerances:									
± 859 W.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission SOURIAU DRG N° SHEET									
8D519K11BA-C 1/2 B A									

ſ	т	۵			т		0	σ	Þ		_
		Contact Layout									
4		$\begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} $									4
 ى	Contact position ID X-axis (mm) A +.105 (2.67) B +.250 (6.35) C +.275 (6.39) D +.179 (4.55) E +.000 (0.00) F 179 (4.55)	(mm) ID (mm) (t) +.260 (6.60) G 275 (6.99) 05. +.132 (3.35) H 250 (6.35) +.13. 053 (1.35) J 105 (2.67) +.260 215 (5.46) K +.000 (0.00) +.100 281 (7.14) L +.000 (0.00) 090 215 (5.46)	0 (6.60)								3
	_										0
	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)										
N							PN: 80		ction & Control List Not Listed		2
						A 18-10-20 ISS DATE	16 First Release Latest modification - by			MOD N°	-
						Designed By: TITLE	Date:	ainless Steel Plug 8	CUSTOMER DRAWING 8D series		_
_						SCALE NA	-{	al linear ances: 	NPRDS / PROJECT 859		1
						SOURIA	U WWW.SOUR	IAU.COM	This document is the prop SOURIAU it must not be reproduc communicated without pe	ed or	
						FORMAT A3	8D5	RIAU DRG N° 519K11BA-C		SHEET 2/2	
	Н	G		F	E	/ D	C	В	I A		