			0		A
	ØS				
s			LAYOUT SHOWN AS E	XAMPLE	
CHARACTERISTICS	Keying Shown as example				
<ul> <li>-Standard : Based on MIL-DTL-38999 Series III</li> <li>-Shell Material : Composite</li> <li>-Shell Plating : Olive drab Cadmium</li> <li>-Insulator : Thermoplastic</li> <li>-Contacts : Copper Alloy</li> <li>-Seals &amp; Grommet : Silicon Elastomer</li> <li>-Contact Plating : Gold over copper Alloy 0.8µm minimum</li> </ul>	Connector dimension       Dim     Nominal       ØS     41.7 Max       Z'     31.5 Max       VV THREAD     M31x1-6g		SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either o (professional recommendat Countr FR	hich does not comply with f the Parties or by a third party ion, technical notice.)	
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D521J11PBL		
-Temperature Range : -65°C to +175°C -Salt Spray : 2000 hours - Mass : 30.8 g ± 10%		A 06-10-201 ISS DATE Designed By:	L6 First Release Latest modification - by Date:	CUSTOMER DRAWIN	MOD N°
		TITLE	TITLE Composite Plug 8D series		
BASIC SERIES:     8D     5     -     21       SHELL TYPE     : Plug with RFI Shielding     -     21       CONTACT TYPE     : Standard Crimp Contact     -	J 11 P B L Delivered W/O Co ORIENTATI	ON : B SOURIAU	General linear Tolerances: ±	COM NPRDS / PROJECT 859 This document is the SOURIAL it must not be repu communicated witho	J roduced or
SHELL SIZE : 21	CONTACT TYPE : PIN(500 M	atings)			

r	Ŧ	۵	н <b>г</b>	m		0	
		Contact Layout					
4	-x -	$ \begin{array}{c} \varepsilon & + Y \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & $					
	B         + 306 (7.77)           C         + 348 (8.84)           D         + 227 (5.77)           E         + 000 (0.00)           F         - 227 (5.77)           Shell         Arrangement no.         Nu<	Y-axis (mm)         position ID         X-axis (mm)         Y-axis (mm)           +.332 (8.43)         G        348 (8.84)        061 (1.55)           +.177 (4.50)         H        306 (7.77)         +.177 (4.50)          061 (1.55)         J        121 (3.07)         +.322 (8.43)          270 (6.86)         K         +.000 (0.00)         +.123 (3.12)          353 (8.97)         L         +.000 (0.00)        115 (2.92)          270 (6.86)					
ى س							
	1						
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda	
2						Count FR	
						PN: 8D521.	
					A 06-10-20	16 First Release	
					ISS DATE Designed By:	Latest modification - by Date:	
					TITLE	Comp	
<u> </u>					SCALE	General linear Tolerances:	
					SOURIA	OURIAU WWW.SOURIAU.	
					FORMAT A3	SOURIAL 8D521J2	
Ĺ	Н	G	F	E	D	C	

