т <u>о</u>	т   т		0			
	205					
			LAYC	OUT SHOWN AS EXAMPLE		
	Keying Shown as example					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal	-				
-Shell Material     : Composite       -Shell Plating     : Olive drab Cadmium       -Insulator     : Thermoplastic       -Contacts     : Copper Alloy	ØS         41.7 Max           Z'         31.5 Max           VV THREAD         M31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum				Country Juris FR	diction & Control List Not Listed	
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D521J11SCL			
-Temperature Range : -65°C to +175°C						
-Salt Spray : 2000 hours			A 07-10-2016 First Release ISS DATE Latest modification - by			
Mass : 40.3 g ± 10%		ISS Designed		- by	CUSTOMER DRAWING	MOD N°
		т	TITLE Composite Plug 8D series			
BASIC SERIES: 8D 5 - 21 J SHELL TYPE : Plug with RFI Shielding	11 S C L Delivered W	/O Contacts NA		General linear Tolerances: ±	NPRDS / PROJECT <b>859</b>	
CONTACT TYPE : Standard Crimp Contact			SOURIAU         This document is the property of SOURIAU           it must not be reproduced or			
SHELL SIZE : 21	CONTACT TYPE : SOCKET(5		AT		communicated without pe	rmission SHEET
PLATING : J = Olive drab Cadmium	CONTACT LA	A3		SOURIAU DRG N° 8D521J11SCL-C		1/2
				00021111005-0		

r	Ŧ	۵	н <b>г</b>	m		0	
		Contact Layout					
4	-x -	$ \begin{array}{c} \varepsilon & + Y \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & $					
	B         + 306 (7.77)           C         + 348 (8.84)           D         + 227 (5.77)           E         + 000 (0.00)           F         - 227 (5.77)           Shell         Arrangement no.         Nu<	Y-axis (mm)         position ID         X-axis (mm)         Y-axis (mm)           +.332 (8.43)         G        348 (8.84)        061 (1.55)           +.177 (4.50)         H        306 (7.77)         +.177 (4.50)          061 (1.55)         J        121 (3.07)         +.322 (8.43)          270 (6.86)         K         +.000 (0.00)         +.123 (3.12)          353 (8.97)         L         +.000 (0.00)        115 (2.92)          270 (6.86)					
ى س							
	1						
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda	
0						Count FR	
						PN: 8D521.	
						016 First Release	
_					ISS DATE Designed By:	Latest modification - by Date:	
					TITLE	Comp	
<u> </u>					SCALE NA	General linear Tolerances: ±	
					SOURIA	OURIAU WWW.SOURIAU.	
					FORMAT A3	SOURIAL 8D521J2	
l	Н	G	F	E	D	C	

