	т (п		0	₩	A
Z'	ØS				
			LAYOUT SHOWN	AS EXAMPLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension Dim Nominal]			
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	DimNominalØS41.7 MaxZ'31.5 MaxVV THREADM31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed		
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D521M11BE		
-Temperature Range : -65°C to +200°C		A 07.10	2016 First Release		
-Salt Spray : 2000 hours -Mass : 57.9 g ± 10%		ISS DAT Designed By:		CUSTO	MOD N
		TITLE	TITLE Composite Plug 8D serie		25
BASIC SERIES: 8D 5 - 21 M SHELL TYPE : Plug with RFI Shielding	11 B E	SCALE NA	General lir Tolerance ±	es:	DS / PROJECT 859
CONTACT TYPE : Standard Crimp Contact ORIENTATION : E			SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission		
SHELL SIZE : 21					
SHELL SIZE : 21 PLATING : M = Nickel	CONTACT LAY	OUT : 21-11 FORMAT A3	SOURI	AU DRG N°	SHEET

r	Ŧ	۵	н г	m		0
		Contact Layout				
4	-x -	$ \begin{array}{c} \varepsilon & +^{\vee} \\ & & \\ & & \\ & & \\ & & \\ & \\ & \\ & \\ $				
	B + 306 (7.77) C + 348 (8.84) D + 227 (5.77) E + 000 (0.00) F - 227 (5.77) Shell Arrangement no. Nu<	Y-axis (mm) position ID X-axis (mm) Y-axis (mm) +.332 (8.43) G 348 (8.84) 061 (1.55) +.177 (4.50) H 306 (7.77) +.177 (4.50) 061 (1.55) J 121 (3.07) +.322 (8.43) 270 (6.86) K +.000 (0.00) +.123 (3.12) 353 (8.97) L +.000 (0.00) 115 (2.92) 270 (6.86)	s			
ယ						
	1					
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D521
						16 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Comp
<u> </u>					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIAL 8D521N
Ĺ	Н	G	F	E	D	C C

