ב <u>ס</u>			0	₩	Þ	
	ds the second se					
			LAYOUT SHOWN AS E	XAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension	]				
-Standard : Based on MIL-DTL-38999 Series III         -Shell Material       : Composite         -Shell Plating       : Nickel         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy         -Seals & Grommet       : Silicon Elastomer	DimNominalØS41.7 MaxZ'31.5 MaxVV THREADM31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country         Jurisdiction & Control List FR         Not Listed           PN: 8D521M16BBB			
<ul> <li>-Contact Plating : Gold over copper Alloy 0.8µm minimum</li> <li>-Durability : 500 Mating cycles</li> <li>-Delivered with Souriau contacts and Accessories</li> </ul>						
-Temperature Range : -65°C to +200°C						
-Salt Spray       : 2000 hours         - Mass       : 50.4 g ± 10%		A 07-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	CUSTOMER DR	MOD N°	
		TITLE	TITLE Composite Plug 8D series			
BASIC SERIES: 8D 5 - 21 M SHELL TYPE : Plug with RFI Shielding	16 B B	SCALE	General linear Tolerances:	NPRDS / PRC <b>859</b>	DJECT	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21				SOURIAU       This document is the property of SOURIAU         SOURIAU       It must not be reproduced or communicated without permissi		
	L	FORMAT			CUEFT	
PLATING : M = Nickel	CONTACT LA	A3	SOURIAU 8D521M		SHEET	

r	т	െ	<del>ار</del> (	m		0	
		Contact Layout					
4		$ \begin{array}{c} & & & & & \\ & & & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & $					
	Contact position ID         Loca           A         +.118 (3.00)           B         +.271 (6.88)           C         +.341 (8.66)           D         +.308 (7.82)           E         +.182 (4.62)           F         +.000 (0.00)           G        182 (4.62)	Contacts           Contact position         Location           Y-axis         Domine 1           y-axis         Contact position           Y-axis         Domine 1           y-axis         Domine 1           y-axis         Y-axis           y-axis         Y-axis           y-axis         Y-axis           y-axis         Position           y-axis         Position <t< td=""><td></td><td></td><td></td><td></td><td></td></t<>					
ω	H308 (7.82) Shell Arrangement Nu size no. co		]				
	+					SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor	oducts w / either o
N						PN: 8D	Count FR 0521
					A 07-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
					SCALE NA	Genera 	Compo al linear rances: ±
					FORMAT	U WWW.SOUR SOU	
		<u> </u>	<b>-</b>	r (	A3	8D5	521N
	Н	l G	F	E	D	C	l

