т a a a a a a a a a a a a a a a a a a a								
	LAYOUT SHOWN AS EXAMPLE							
Keying Shown as example								
CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal								
-Standard : Based on MIL-DTL-38999 Series III Dim Nominal -Shell Material : Aluminium ØS 41.7 Max -Shell Plating : Black Zinc Nickel Z 31 Max -Insulator : Thermoplastic VV THREAD M31x1-6g -Contacts : Copper Alloy : Solicon Elastomer . -Seals & Grommet : Silicon Elastomer . . -Contact Plating : Gold over copper Alloy 0.8µm minimum . .								
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	PN: 8D521Z42SA							
-Temperature Range : -65°C to +175°C	A 12-10-2016 First Release							
-Salt Spray : 500 hours	ISS DATE Latest modification - by MOD) N° _						
	Designed By: Date: CUSTOMER DRAWING							
	TITLE Aluminium Plug 8D series							
BASIC SERIES: 8D 5 - 21 Z 42 S A SHELL TYPE : Plug with RFI Shielding - - 21 Z 42 S A	SCALE General linear NPRDS / PROJECT NA Tolerances: 859							
CONTACT TYPE : Standard Crimp Contact ORIENT	ATION : A SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or							
SHELL SIZE : 21 CONTACT TYPE : SOCKET(500 PLATING : Z = Black Zinc Nickel CONTACT LAYOU								
	A3 8D521Z42SA-C 1/2							

	т		Q		т	т		0	
4		4	ct Layout						
		Ctc A	0 6.	γ 19 .19					
ယ									
	F							the Specifications i	of the Products wh issued by either o mal recommendat
23								Р	Countr FR N: 8D5212
							A 12-10-201 ISS DATE Designed By:	.6 First Release Latest modification Date:	1 - by
1							SCALE NA		Alumin General linear Tolerances: ±
							SOURIAL		SOURIAU.C
	Н		G		F	 E	A3	С	SOURIAU 8D521Z4

