	T Q M		0	₩ >		]
4	Z					4
ω			LAYOUT SHOWN AS EX	KAMPLE		3
	Keying Shown as example					
	CHARACTERISTICS Connector dimension Standard : Based on MIL-DTL-38999 Series III Dim Nominal					
    	Standard : Based on MIL-DTL-38999 Series III     Dim     Nominal       Shell Material     : Aluminium     ØS     44.9 Max       Shell Plating     : Nickel     Z     31 Max       Insulator     : Thermoplastic     VV THREAD     M34x1-6g       Contacts     : Copper Alloy     Seals & Grommet     : Silicon Elastomer       Contact Plating     : Gold over copper Alloy 0.8µm minimum     Image: Second	due to a use of the Products wh the Specifications issued by either of (professional recommendati	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed			
	Durability       : 500 Mating cycles         Delivered with Souriau contacts and Accessories		PN: 8D523F06AE			
	Temperature Range: -65°C to +200°CSalt Spray: 48 hours	A 06-10	0-2016 First Release			
		ISS DA Designed By:	ATE Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE	Aluminium Plug 8D series			
-	BASIC SERIES: 8D 5 - 23 F 06 A E BHELL TYPE : Plug with RFI Shielding	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		-
	CONTACT TYPE : Standard Crimp Contact CONTACT TYPE : 23 CONTACT TYPE : PIN(500 M	SOOKI	SOURIAU WWW.SOURIAU.COM it must not be r communicated wit			
-	PLATING : F = Nickel CONTACT LAYOUT	: 23-06 FORMAT	SOURIAU		SHEET	_
	H G F E	A3	8D523F0	D6AE-C	1/2	
		U				

-	Т	۵	г п	m	D	0
		Contact Layout				
4		06				
	6	5#8 Concentric Twinax Service M				
_		23-06	1			
	Ctc	X Y	-			
	A	0 9.24	1			
	В	8.81 2.87	]			
	С	5.43 -7.49				
ယ	D	-5.43 -7.49	-			
	E	-8.81 2.87	-			
	F	0 0				
						SOURIAU shall not be liable for an
						due to a use of the Products w
						the Specifications issued by either o
						(professional recommenda
N						Count FR
						PN: 8D523
					A 06-10-20	16 First Release
					ISS DATE	
					Designed By:	Date:
					TITLE	Alumir
					SCALE	General linear
<b>_</b>					NA	Tolerances:
					SOURIA	WWW.SOURIAU.
						SOURIAU
l			1		A3	8D523F
	Н	G	F	I E	D	C

