	도   G			0	Φ		
Schultz Stander 1: Based on Miller 1: Saged Series III    Schultz Stander 1: Based on Miller 1: Saged Series III    Schultz Schutz Schultz Schultz Schutz Schultz Schultz Schultz Schultz Schultz							
CHARACTERISTICS    9 standard : Based on ML/DT-38999 Series III    Shell Material  :: Composite    Shell Material  :: Composite    Shell Material  :: Composite    Shell Material  :: Composite    Shell Material  :: Shell Material    Shell Material  :: Composite    Shell Material  :: Composite    Sourcal Value  : Composite    Sourcal Value  : Sourcal Value    Sourcal Value  : Sourcal Value    Oblight Standard  : Sourcal Value    Sourcal Value  : Sourcal Value <td< td=""><td></td><td></td><td></td><td>LAYOUT SHO</td><td>WN AS EXAMPLE</td><td></td><td></td></td<>				LAYOUT SHO	WN AS EXAMPLE		
BASIC SERIES:  8D  5  -  23  J  06  B  D    SHELL TYPE : Plug with RFI Shielding	-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Composite-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories-Temperature Range: -65°C to +175°C	DimNominalØS44.9 MaxZ'31.5 MaxVV THREADM34x1-6g	ISS DAT	due to a use of the Pro the Specifications issued by (professional recon <b>PN: 8E</b> 2016 First Release E Latest modification - by	ducts which does not comply either of the Parties or by a t mendation, technical notice Country Jurisdictio FR NC	v with chird party .) n & Control List ot Listed MOD	DN°
BASIC SERIES:  8D  5  -  23  J  06  B  D    SHELL TYPE : Plug with RFI Shielding  SCALE  SCALE  SCALE  Tolerances:  859    CONTACT TYPE : Standard Crimp Contact  ORIENTATION : D  ORIENTATION : D  SOURIAU  SOURIAU  This document is the property of SOURIAU    SHELL SIZE : 23  SHELL SIZE : 23  SOURACT TYPE : SOCKET(500 Matings)  SOURIAU  WWW.SOURIAU.COM  This document is the property of SOURIAU							
A3 8D523106BD-C 1/2	SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact	OR CONTACT TYPE : SOCKE	IENTATION : D (500 Matings)	Genera Tolera ±	I linear inces:  IAU.COM	NPRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or communicated without permission	

F	т	۵	г	m		0
		Contact Layout				
4		06				
	,	6#8 Concentric				
		Twinax Service M				
_		23-06	]			
	Ctc	X Y	]			
	A	0 9.24	-			
	В	8.81 2.87	-			
	C	5.43 -7.49	-			
ယ	D E	-5.43 -7.49 -8.81 2.87	-			
	F	0 0	-			
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N					<b></b>	Count FR
						PN: 8D523
					A 06-10-20	116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Compo
_					SCALE	General linear Tolerances:
					SOURIA	
					FORMAT A3	SOURIAU 8D523J0
L	Н	G	F	E	/ D	C
			1			

