	ت ا	۳	m		0	₩	Þ	
Characteristics Source of the Products which does not comply with a sexample Shell Material ::::::::::::::::::::::::::::::::::::								4
CHARCTERISTICS Standard: Based on MU-DTL-38999 Series II Shell Material: Micro M					LAYOUT SHOWN AS EX	AMPLE		3
Standard : Based on MIL DTL-38099 Series III Dimeter Working Shell Material: ::: Auminium Shell Material: ::: Auminium Shell Material: ::: Auminium Shell Material: ::: Auminium -Shell Patrice: ::: ::: ::: ::: ::: ::: ::: ::: :::		Keying Shown as e	example					
Shell Material :: Auninium Shell Material :: Auninium Shell Material :: Olive drab Cadmium -Insulator :: Olive drab Cadmium -Insulator :: Comparative Silicon Elastomer -Contact Plang :: Gold over copper Alloy QBum minimum -Durability ::: Solid over copper Alloy QBum minimum -durational contact and Accessories ::: Thermoperature Range ::: 45°C to +175°C -sait Spray ::: Solid contact SHELL TYPE :: Plug with RFI Shielding :: Customer Customer Rawing Contact TYPE :: Standard Crimp Contact		F						
-Shell Plating ::::::::::::::::::::::::::::::::::::								<u> </u>
 Contact Plating :: 60ld over copper Alloy 0.8µm minimum Durability :: 500 Mating cycles Deleivered with Souriau contacts and Accessories Temperature Range :: 65°C to ±175°C Salt Spray :: 500 hours Mass :: 72.73 g ± 10% Assic SERIES: 8D 5 _ 23 W 55 S D Basic SERIES: 8D 5 _ 23 W 55 S D Basic SERIES: 8D 5 _ 23 W 55 S D Basic SERIES: 8D 5 _ 23 W 55 S D CONTACT TYPE : Standard Crimp Contact But INTRE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 23 CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 23 CONTACT TYPE : Standard Crimp Contact Souriau W w = 0 live drab Cadmium CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOURIAU W w = 0 live drab Cadmium CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOURIAU W w w = 0 live drab Cadmium CONTACT TYPE : SOURIAU SOURIAU DRG N° SHEET Tainage Support of Street and the propure of Street and Street	-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	A Luminium Z 31 Max -Shell Material : Aluminium Z 31 Max -Shell Plating : Olive drab Cadmium VV THREAD M34x1-6g -Insulator : Thermoplastic VV THREAD M34x1-6g -Contacts : Copper Alloy : Copper Alloy : Copper Alloy						
-Durability :: 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range :: 65°C to +175°C -salt Spray :: 500 hours -Mass : 72.73 g ± 10% BASIC SERIES: 8D 8D 5 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SZE 23 VW 55 D ORIENTATION : D SHELL SZE : SOURIAU WWW.SOURIAU.COM This document is this property of communicated without permission CONTACT TYPE : Standard Crimp Contact SHELL SZE : ONTACT LAYOUT : 23-55 PLATING : W = Olive drab Cadmium		m minimum						2
-Salt Spray : 500 hours -Mass : 72.73 g ± 10% BASIC SERIES: 8D 5 23 W 55 D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact NPRDS / PROJECT SHELL SIZE : 23 CONTACT TYPE : Standard Crimp Contact NPRDS / PROJECT 859 PLATING : W = Olive drab Cadmium CONTACT TYPE : Sourial WWW.SourialU.COM This document is the property of communicated without permission PLATING : W = Olive drab Cadmium SOURIAU DRG N° SHEET A3 SOURIAU DRG N° SHEET A3 SDURIAU DRG N° SHEET	-Durability : 500 Mating cycles				PN: 8D523W	/55SD		
-Salt Spray : 500 hours -Mass : 72.73 g ± 10% BASIC SERIES: 8D 5 - 23 W 55 5 D SHELL STZE : 23 PLATING : W = Olive drab Cadmium DATION : D SHELL STZE : 23 CONTACT TYPE : SOCKET(500 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) DATION : D SHELL STZE : 23 CONTACT LAYOUT : 23-55 D CONTACT LAYOUT : 23-55 CONTACT LAYOUT : 23-55				A 07-10-2016	First Release			1
Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D 5 23 W 55 5 D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact 0RIENTATION : D General linear Tolerances: ± NPRDS / PROJECT SHELL SIZE : 23 CONTACT TYPE : Standard Crimp Contact CONTACT TYPE : SOCKET(500 Matings) This document is the property of SOURIAU SOURIAU SOURIAU SOURIAU it must not be reproduced or communicated without permission PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) FORMAT SOURIAU DRG N° SHEET SHEET A3 8D523W55SD-C 1/2					Latest modification - by			1
BASIC SERIES: 8D 5 - 23 W 55 S D SCALE Tolerances: 859 *- 859 SHELL TYPE : Standard Crimp Contact ORIENTATION : D ORIENTATION : D SOURIAU This document is the property of SOURIAU SOURIAU it must not be reproduced or communicated without permission SHELL SIZE : W Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) FORMAT SOURIAU DRG N° SHEET A3 8D523W55SD-C 1/2	-IVIdSS . 72.75 g I 10%					CUSTOMER DRA		
BASIC SERIES. SUP SUP Sup 3 2 W 35 3 D Introduction of the property of source of communicated without permission 859 1 SHELL SIZE : 23 SHELL SIZE : 23 CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 23-55 SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 23-55 FORMAT SOURIAU DRG N° SHEET A3 8D523W55SD-C 1/2	TITLE Aluminium Plug 8D series					um Plug 8D series		
CONTACT TYPE : Standard Crimp Contact ORIENTATION : D SOURIAU This document is the property of SOURIAU. SHELL SIZE : 23 CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 23-55 SOURIAU WWW.SOURIAU.COM It must not be reproduced or communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 23-55 FORMAT SOURIAU DRG N° SHEET A3 8D523W55SD-C 1/2		23 W 55 S D		-			ECT	1
PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 23-55 FORMAT SOURIAU DRG N° SHEET A3 8D523W55SD-C 1/2	CONTACT TYPE : Standard Crimp Contact			- SOURIAU	WWW.SOURIAU.CO	OM it must not be	URIAU e reproduced or	
A3 SOOKAO DKG N 1/2		L		—				1
		I	CUNTACT LATUUT : 23	55				1
		E						l.

ſ	Ŧ	۵	н т	m	D	O
		Contact Layout				
4	-XL N	$\begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} $				
	B +.225 (5.72) C +.336 (8.53) D +.450 (11.43)	Contacts (Insert arrangement 23-55) On Contact position ID Location Y-axis (mm) Contact position ID X-axis (mm) Y-axis (mm) +455 (11:56) f -112 (2.84) -325 (8.26) +326 (8.26) h -336 (8.53) -195 (4.95) +130 (3.30) i -336 (8.53) -065 (1.65) -130 (3.00) j -336 (8.53) +055 (1.55) -325 (8.26) m -225 (5.72) +260 (6.60) -332 (8.25) m -225 (5.72) +260 (6.60) -330 (9.94) n -112 (2.84) +325 (8.26) -326 (9.94) n -225 (5.72) +260 (6.60) -390 (9.94) n -112 (2.84) +325 (8.26)				
ω	K 112 (2.84) L 225 (6.72) M 336 (8.53) N 450 (11.43) P 450 (11.43) S 336 (8.53) T 225 (6.72) U 112 (2.84) V +.000 (0.00) W +.112 (2.84) X +.225 (6.72) Y +.336 (8.53)	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$				
	size no. con	ber of Size Service Contact Superseder tacts contacts rating location 5 20 I All	5			SOURIAU shall not be liable for a
						due to a use of the Products w the Specifications issued by either (professional recommenda
N						Coun FR
						PN: 8D523
					A 07-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:
					TITLE	Alumi
→					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIAL 8D523V
L	Н	G	F	E	D	C

