	m (0	σ	A	
Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z						-
			LAYOUT SHOWN AS EXA	AMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	DimNominalØS44.9 MaxZ31 MaxVV THREADM34x1-6g		SOURIAU shall not be liable for any due to a use of the Products which the Specifications issued by either of t (professional recommendation)	ch does not comply with he Parties or by a third pa		-
-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum			Country FR	Jurisdiction & Co Not Listed		
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D523Z0)6PCL		
-Temperature Range <u>-</u> -65°C to +175°C		A 07-10-2016	First Release			
-Salt Spray : 500 hours		ISS DATE Designed By:	Latest modification - by Date:	сизтом	MOD N	۷°
		TITLE	TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 23 Z SHELL TYPE : Plug with RFI Shielding - - - 23 Z	06 P C L Delivered W/O Conta	acts NA	General linear Tolerances: ±		S / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact	ORIENTATION CONTACT TYPE : PIN(500 Matir	- SUURIAU	WWW.SOURIAU.CO	DM it m	locument is the property of SOURIAU ust not be reproduced or unicated without permission	
SHELL SIZE · 23		1.001		commu		
SHELL SIZE : 23 PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 23	3-06 FORMAT	SOURIAU I	DRG N°	SHEET	тΙ

r	т	۵	г	m		0
		Contact Layout				
		06				
4		620				
		00				
		6#8 Concentric Twinax Service M				
		23-06]			
	Ctc	X Y				
	А	0 9.24]			
	В	8.81 2.87	-			
	С	5.43 -7.49	-			
ယ	D	-5.43 -7.49				
	E F	-8.81 2.87 0 0	-			
]			
	l					
						SOURIAU shall not be liable for an
						due to a use of the Products w
						the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D5232
					A 07-10-20	16 First Release
					ISS DATE	Latest modification - by
					Designed By:	Date:
					TITLE	Alumir
					SCALE	General linear
→					NA	Tolerances:
					SOURIA	U WWW.SOURIAU.C
					FORMAT	
					A3	SOURIAU
L					1	8D523Z0
	Н	G	l F	E	D	C

				4		
				3		
whic r of tl datio ntry R	n, technical n	mply with by a third party		2		
			MOD N°			
customer drawing						
r		NPRDS / PROJECT				
	859					
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
	DRG N°		SHEET 2/2			
200	BPCL-C	A	212	J		
	U					

Φ