ſ	I		G		П			ш		D		O
4	B On flat	R 22.6 Max		V Thread		S		ØA				
					Keying S	Shown as ex	ample					
2	CHARACTERISTICS-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Stainless Steel-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum-Durability: 500 Mating cycles			Connector dimension           Dim         Nominal           A         34.9±0.3           B         19.07+0.1/-0.15           R         32.5Max           S         31.8±0.4           W         2.2+0.9/-0.1           VV THREAD         M15x1-6g							SOURIAU shal due to a us the Specification (profes	
	-Delivered without Sou -Temperature Range -Salt Spray		۴C							A ISS Designe	DATE	First Release Latest modifica Date
			_ 1 _ 1 _ 1	. 1	1	. 1				SCAI	FITLE	
<b>_</b>	BASIC SERIES: SHELL TYPE : Jam nut CONTACT TYPE : Sta	Receptacle	D 7 -	11 S	02 P	N L		ORIEI	V/O Contacts	NA		₩wv
	SHELL SIZE : 11 PLATING : S =	Nickel					CON	ITACT TYPE : PIN(5		FORM		
	Н		G		F			E	1	A3	5	С

 $\forall$ 

	σ		2	D			
					4		
LAYOUT SHOWN AS EXAM	MPLE				3		
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D711S02PNL							
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series							
General linear Tolerances:       NPRDS / PROJECT         ±       859         W.SOURIAU.COM       This document is the property of SOURIAU it must not be reproduced or communicated without permission							
SOURIAU D 8D711S02	PNL-C	· 		SHEET 1/2			
l	В			A			

ſ	Q I	т (Г		B		
4	Contact Layout		Panel cutout JAM NUT RECEPTACLE (TYPE 7)			4
	Contacts (Insert arrangement 11-2)         Contact position ID       X-axis       Y-axis (mm)         A       +.095 (2.41)       +.000 (.00)         B      095 (2.41)       +.000 (.00)         Shell       Arrangement no.       Number of contacts       Size       Service rating       Contact location         11       -2       2       16       I       All		Dim Nomina B 19.59+0/-0			
ω			ØC 20.96+0.25			3
2			due to a use of the Pro the Specifications issued by	Def for any non-conformity or damage         oducts which does not comply with         v either of the Parties or by a third party         mmendation, technical notice.)         Country       Jurisdiction & Control List         FR       Not Listed		2
		A 30-09-2016 First Release				
		ISS       DATE       Latest modification - by         Designed By:       Date:       Date:       CUSTOMER DRAWIN         TITLE       Stainless Steel Receptacle 8D series				
<b>_</b>			SCALE       General linear       NPRDS / PROJECT         NA       Tolerances:       859         SOURIAU       WWW.SOURIAU.COM       This document is the provident of the must not be reprovident of the mus			1
				RIAU DRG N° /11S02PNL-C	SHEET 2/2	
L	H G I	FEE	D C	BA		