	T Q T	m	D	0	B	
4	R 22.6 Max (t) (t) (t) (t) (t) (t) (t) (t) (t) (t)	S		<image/> <image/>	NPLE	4
	Keying Sh CHARACTERISTICS Standard : Based on MIL-DTL-38999 Series III	nown as example Connector dimension Dim Nominal				
2	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum-Durability: 500 Mating cycles-Delivered without Souriau contacts-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours	A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g	A 01-10-2016 ISS DATE	SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of the (professional recommendation, Country FR PN: 8D711WOS First Release Latest modification - by	does not comply with Parties or by a third party technical notice.) Jurisdiction & Control List Not Listed	2
	-Mass : 17.32 g ± 10%		Designed By:	Date:	CUSTOMER DRAWING	
TITLE Aluminium Receptac					_	
<u> </u>	BASIC SERIES: 8D 7 - 11 W 05 P SHELL TYPE : Jam nut Receptacle - - 11 W 05 P	N L Delivered W/O Contacts	SCALE -{	General linear Tolerances: ±	NPRDS / PROJECT 859	1
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENTATION : N CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.CO	This document is the property of SOURIAU it must not be reproduced or communicated without permission	
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 11-05	format A3	SOURIAU D 8D711W05		
L	H G F	E	D	C	BA	-

Г	٦ D	т (П		
4	Contact Layout x x x x x x x x		Damel cutout JAM NUT RECEPTACLE (TYPE 7)	4
	Contacts (Insert arrangement 11-5) Contact position Contact location (mm) Y-axis (mm) A +.065 (1.65) +.056 (1.42) B +.113 (2.87) 065 (1.65) C +.000 (0.00) 130 (3.30) D 113 (2.87) 065 (1.65) E 065 (1.65) +.056 (1.42) Shell Arrangement Number of size Size Service Contact			
w	11 -5 5 20 I All MS20050-5		DimNominalB19.59+0/-0.25ØC20.96+0.25/-0	3
			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	
2			Country Jurisdiction & Control List FR Not Listed PN: 8D711W05PNL A 01-10-2016 First Release Image: Country of the second secon	2
			ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING	
			TITLE Aluminium Receptacle 8D series	
<u> </u>			SCALE General linear NPRDS / PROJECT NA Tolerances: 859 SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission communicated without permission	1
			FORMATSOURIAU DRG N°SHEETA38D711W05PNL-C2/2	
_	H G	F E	D C B A	