ſ	T	Q	т	m	D		O
4	R 22.6 Max	N Thread					
2	CHARACTERISTICS         -Standard : Based on NIL-DTL-38999 Serie         -Shell Material       : Stainless Steel         -Shell Plating       : Passivated         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy         -Seals & Grommet       : Silicon Elastomet         -Contact Plating       : Gold over copp			Connector dimension           Dim         Nominal           A         38.1±0.3           B         23.82+0.1/-0.15           R         32.5Max           S         34.9±0.4           W         2.2+0.9/-0.1           VV THREAD         M18x1-6g			SOURIAU sha due to a us the Specificatio (profes
	-Durability: 500 Mating cyc-Delivered without Souriau contacts-Temperature Range: -65°C to +200°C-Salt Spray: 500 hours				1	A 28-09-2016 SS DATE esigned By:	First Release Latest modifica Date
<b></b>	BASIC SERIES:       8D         SHELL TYPE       : Jam nut Receptacle         CONTACT TYPE       : Standard Crimp Conta         SHELL SIZE : 13       13		K 04 P E L	Delivered W ORIE CONTACT TYPE : PIN(5	500 Matings)	TITLE SCALE NA SOURIAU	- - - - - - - - - - - - - - - - - - -
	PLATING : K = Passivated			CONTACT LAY	1001:13-04	A3	

F

G

Н

 $\forall$ 

D

Е

	0	σ	A				
				4			
LAYOUT SHOWN AS EXAMPLE							
SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed							
PN: 8D713K04PEL							
TE Latest modification - by MOD N°							
Date:     CUSTOMER DRAWING       Stainless Steel Receptacle 8D series							
-		al linear ances:	NPRDS / PROJECT 859				
AU WWW.SOURIAU.COM it must not be reproduced or communicated without permission							
SOURIAU DRG N° SHEET							
8D713K04PEL-C 1/2							
C B A							

Г	٦ G	г	т		0		•	7
4	Contact Layout A A A A A A A A			JAM	Panel cutout NUT RECEPTACLE (TYPE 7)			4
	Contacts (Insert arrangement 13-4)           Location           Contact position ID         Location           Contact position ID         (mm)         Location           A         +.000 (0.00)         +.146 (3.71)         +.035 (0.89)           C         +.000 (0.00)        083 (2.11)           D        146 (3.71)         +.035 (0.89)           Sheli         Arrangement         Number of contacts         Size         Service rating         Contact         Supersed           13         -4         4         16         I         All         MS20051				ØC			
ω					DimNominalB24.26+0/-0.25ØC25.65+0.25/-0			3
					SOURIAU shall not be liable for an due to a use of the Products wl the Specifications issued by either o (professional recommenda	nich does not comply with f the Parties or by a third party		
N					PN: 8D713	Not Listed		2
				A 28-09-2016 Fi				
				ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
				TITLE	TITLE         Stainless Steel Receptacle 8D series			
				SCALE	General linear Tolerances: ±	NPRDS / PROJECT <b>859</b>		
				SOURIAU	SOURIAU WWW.SOURIAU.COM This document is the proper SOURIAU it must not be reproduced communicated without perm			
				FORMAT	SOURIAU	DRG N°	SHEET	
			_	A3	8D713K0		2/2	
	H I G	I F	I E	D	C	B I A	L Contraction of the second	