ſ	T	Q	П	m	D		C		
4	R 22.6 Max	M Thread					L.		
	Keying Shown as example								
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Set -Shell Material : Stainless Stee -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastor -Contact Plating : Gold over cop -Durability : 500 Mating co	l c mer oper Alloy 0.8μm minimum		Connector dimension Dim Nominal A 58.7±0.3 B 42.85+0.1/-0.15 R 32.5Max S 55.6±0.4 W 3+0.9/-0.1 VV THREAD M37x1-6g			SOURIAU shal due to a us the Specificatior (profess		
	-Delivered with Souriau contacts and A -Temperature Range : -65°C to +200 -Salt Spray : 500 hours	ccessories			15	A 04-10-2016 S DATE Signed By:	First Release Latest modificat Date		
_	BASIC SERIES: 8D 7 - 25 S 61 B E SHELL TYPE : Jam nut Receptacle		S 61 B E		NTATION : E	TITLE SCALE NA OURIAU	- - - www		
	SHELL SIZE : 25 PLATING : S = Nickel			CONTACT TYPE : SOCKET(5		ORMAT			
						A3			
L	Н	G	F	E	D		С		

B		А			
				4	
LAYOUT SHOWN AS EXAMPLE				3	
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D725S61BE					
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series					
General linear Tolerances: ± NPRDS / PROJECT 859 859 W.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or					
SOURIAU DRG 8D725S61BE- B	N°	nunicated without per	mission SHEET 1/2		

ſ	Т	۵	П	П	D	0	σ		Þ	ı
		Contact Layout				Panel cutout				
4	- <u>×</u> ($ \begin{array}{c} \begin{array}{c} & & & \\ & & & & \\ & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\$				JAM NUT RECEPTACLE (TYPE 7)				4
_	Contact position ID (mm) A +.196 (4.96)	Y-axis (mm) Contact position ID (mm) X-axis (mm) Y-axis (mm) +.500 (12.70) 1 +.251 (6.38) 314 (7.100)	98)							
c.	$\begin{array}{cccc} &+413(10.49)\\ & D &+485(12.32)\\ & E &+527(13.39)\\ & F &+536(13.61)\\ & G &+511(12.98)\\ & H &+454(11.53)\\ & J &+368(9.35)\\ & L &+134(3.40)\\ & M &+000(0.00)\\ & N &-134(3.40)\\ & M &+000(0.00)\\ & N &-134(3.40)\\ & P &-259(6.58)\\ & R &-368(9.35)\\ & S &-454(11.53)\\ & T &-511(12.98)\\ & U &-536(13.61)\\ & V &-527(13.39)\\ & W &-485(12.32)\\ & X &-413(10.49)\\ & Y &-314(7.98)\\ & Z &-196(4.98)\\ & a &-068(1.73)\\ & b &+068(1.73)\\ & b &+362(9.19)\\ & \end{array}$	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	1211 63) 98) 41) 24) 17) 45) 19) 22) 59) 66) 10) 25) 53) 92) 78) 92) 53) 25) 53) 92) 53) 92) 53) 92) 53) 92) 53) 93) 94) 95)			Dim Nominal B 43.43+0/-0.25 ØC 44.7+0.25/-0				3
	Shell Arrangement Nun size no. coi	-213 (5.41) iber of Size Service Contact Supers tacts contacts rating location 61 20 I All MS200	edes			SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe (professional recommen	which does not com r of the Parties or by	ply with a third party		
N						Cou		tion & Control List Not Listed		2
						PN: 8D725S61BE				
						6 First Release				
					ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWIN	MOD N° G	
					TITLE Stainless Steel Receptacle 8D series					
_					SCALE	General linea Tolerances:		NPRDS / PROJECT 859		1
					SOURIAU		.COM	This document is the SOURIAL it must not be repr communicated witho	J oduced or	
					FORMAT A3		U DRG N° S61BE-C		SHEET 2/2	
	Н	G	F	E	D	C	В		A	